

PRODUCT SPECIFICATION



- 1. PRODUCT CODE** **AWC2252032**
- 2. DESCRIPTION** 2 Core Flat Twin Sheath 252/.32 (4 B&S) 20mmsq nom.
Oxygen Free Plain Copper Wire.
Non Migratory V-90 PVC Insulated.
Non Migratory 5V-90 PVC Sheathed Automotive cable.
RoHS compliant P.V.C.
Extra Low Voltage Not for Mains connection.
- 3. CONSTRUCTION**
 - 3.1 CONDUCTOR:** 252 strands of 0.32 mm nom. Annealed Copper to AS/NZS1125
drawn from Class 110A copper to AS/NZS1574.

Max. D.C. resistance at 20C: 0.9 ohms / km
 - 3.2 INSULATION:** Coloured Non Migratory V-90 P.V.C. to AS/NZS3808.

Nominal Diameter: 8.3 mm
Nominal Wall Thickness: 1.1 mm
 - 3.3 CORE COLOURS:** 1. Red
2. Black
Laid parallel
 - 3.4 SHEATH:** Coloured Non Migratory P.V.C. type 5-V90 to AS/NZS3808.
Flat configuration

Nominal Diameter: 10.3 x 18.6 mm
Nominal Wall Thickness: 0.96 mm
 - 3.5 IDENTIFICATION:** Nil