TYREE CABLE PTY LTD
A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG RD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
PHONE: 03 (Int. 613) 8791 0333
FAX: 03 (Int. 613) 9791 8732
EMAIL: enquiries@tycab.com.au
WEB: https://www.tycab.com.au/

PRODUCT SPECIFICATION



1. PRODUCT CODE LEC2242

2. DESCRIPTION

2 Core Parallel Webbed (Figure 8) 24/0.2 (0.75mm2).
Plain Annealed Copper Wire.
Non Migratory type V-90 P.V.C Insulated.
Extra Low Voltage. Not for mains connection.
RoHS compliant P.V.C.
Oxygen Free Copper

3. CONSTRUCTION

3.1 CONDUCTOR: 24 strands of 0.2 mm nom. Plain Annealed Copper to AS/NZS 1125 drawn from Class 102 copper to AS/NZS1574

Max. D.C. resistance at 20C:	26.5 ohms / km

3.2 INSULATION: Coloured Non Migratory PVC type V90 to AS/NZS3808.
Parallel Webbed (Figure 8) construction

Nominal Diameter:	2.3 x 5.0 mm
Nominal Wall Thickness:	0.6 mm

3.3 IDENTIFICATION: Polarity ribs on one leg.

Printed: **RACOL SECURITY LEC2242 ACA N1155**