TYCAB AUSTRALIA PTY LTD
A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG RD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
PHONE: 03 (Int. 613) 8791 0333
FAX 03 (Int. 613) 9791 8732
EMAIL: enquiries@tycab.com.au
WEB: http://www.tycab.com.au/

PRODUCT SPECIFICATION



1. PRODUCT CODE: MFS22603

2. DESCRIPTION

2 Core Parallel Webbed (Figure 8) 23/.32 (1.84mmsq).
Tinned Copper Wire.
V90 P.V.C Insulated.
Extra Low Voltage. Not for Mains GPO Connection.
RoHS Compliant P.V.C.
Oxygen Free Copper.

3. CONSTRUCTION

3.1 CONDUCTOR: 23 strands of 0.32mm Tinned Annealed Copper to AS/NZS1125 drawn from Class 110A copper to AS/NZS1574.

Max. D.C. resistance at 20C:	10.2 ohms / km

3.2 INSULATION: Coloured type V90 P.V.C. to AS/NZS3808.
Parallel Webbed (Figure 8) construction.

Nominal Diameter:	3.1 x 6.7 mm
Nominal Wall Thickness:	0.6 mm

3.3 IDENTIFICATION: Nil

APPROVED CABLES INITIATIVE
Cabling a Safer Australia

AUSTRALIAN MADE CABLES LEADING THE WAY