TYCAB AUSTRALIA PTY LTD
A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG RD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
PHONE: 03 (Int. 613) 8791 0333
FAX 03 (Int. 613) 9791 8732
EMAIL: enquiries@tycab.com.au
WEB: http://www.tycab.com.au/

PRODUCT SPECIFICATION



1. PRODUCT CODE: MWS2399032

2. DESCRIPTION

2 Core Flat Twin Sheath 399/0.32 2B&S (32.0mm2).
Tinned Copper Wire.
V90 P.V.C. Insulated & 5V90 P.V.C. Sheathed.
Extra Low Voltage. Not for Mains GPO Connection.
RoHS Compliant P.V.C.
Oxygen Free Copper.

3. CONSTRUCTION

3.1 CONDUCTOR: 399 strands of 0.32 mm nom. Tinned Annealed Copper to AS/NZS1125 drawn from Class 102 copper to AS/NZS1574.

Max. D.C. resistance at 20C:	0.61 ohms / km

3.2 INSULATION: Coloured V90 P.V.C. to AS/NZS3808.

Nominal Diameter:	11.0 mm
Nominal Wall Thickness:	1.7 mm

3.3 CORE COLOURS
1. Red
2. Black

3.4 SHEATH: Black with Red stripe 5V90 P.V.C. to AS/NZS3808
Flat configuration

Nominal Dimensions:	13.0 x 24.0 mm
Nominal Wall Thickness:	0.96 mm

APPROVED CABLES INITIATIVE
Cabling a Safer Australia

AUSTRALIAN MADE CABLES LEADING THE WAY