TYREE CABLE PTY LTD
A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG RD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
PHONE: 03 (Int. 613) 8791 0333
EMAIL: enquiries@tyreecable.com.au
WEB: https://tyreecable.com.au/

PRODUCT SPECIFICATION



1. PRODUCT CODE **ATC72603**

2. DESCRIPTION
7 Core 23/.32 (1.84mmsq).
Oxygen Free Plain Copper Wire.
Non Migratory V-90 PVC Insulated.
Non Migratory 5V-90 PVC Sheathed Trailer cable.
RoHS compliant P.V.C.
60 Volt. Not for Mains connection.

3. CONSTRUCTION

3.1 CONDUCTOR: 23 strands of 0.32 mm nom. Annealed Copper to AS/NZS1125 drawn from Class 102 copper to AS/NZS1574.

Max. D.C. resistance at 20C:	10.3 ohms / km

3.2 INSULATION: Coloured Non Migratory V-90 P.V.C. to AS/NZS3808.

Nominal Diameter:	2.6 mm
Nominal Wall Thickness:	0.4 mm

3.3 LAY UP: 7 Cores laid up.

1. Brown
2. Red
3. Green
4. White
5. Yellow
6. Black
7. Blue

3.4 SHEATH: Coloured Non-Migratory P.V.C. type 5-V90 to AS/NZS3808.

Nominal Diameter:	8.9 mm
Nominal Wall Thickness:	0.6 mm

TYPICAL ROPY TRAILER CABLE FINISH