TYREE CABLE PTY LTD
A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG RD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
PHONE: 03 (Int. 613) 8791 0333
FAX: 03 (Int. 613) 9791 8732
EMAIL: enquiries@tycab.com.au
WEB: https://www.tycab.com.au/

PRODUCT SPECIFICATION



1. PRODUCT CODE ATC7903

2. DESCRIPTION

7 Core 8/.32 (0.64mm2).
Plain Copper Wire
V90 P.V.C. Insulated and 5V90 P.V.C. Sheathed Trailer cable.
Extra Low Voltage. Not for Mains connection.
RoHS compliant P.V.C.
Oxygen Free copper.

3. CONSTRUCTION

3.1 CONDUCTOR: 8 strands of 0.32 mm nom. Annealed Copper to AS/NZS1125 drawn from Class 102 copper to AS/NZS1574.

Max. D.C. resistance at 20C:	29.9 ohms / km

3.2 INSULATION: Coloured V90 P.V.C. to AS/NZS3808.

Nominal Diameter:	2.0 mm
Nominal Wall Thickness:	0.4 mm

3.3 LAY UP: 7 Cores laid up.

1. Brown
2. Red
3. Green
4. White
5. Yellow
6. Black
7. Blue

3.4 SHEATH: Coloured P.V.C. type 5V90 to AS/NZS3808.

Nominal Diameter:	7.3 mm
Nominal Wall Thickness:	0.6 mm

TYPICAL ROPY TRAILER CABLE FINISH